

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NATURAL ISOBUTYL ACETATE

Revision date: 26.03.2025

Product code: 217500

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

NATURAL ISOBUTYL ACETATE

Substance name: NATURAL ISOBUTYL ACETATE
CAS No: 110-19-0
Index No: 607-026-00-7
EC No: 203-745-1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

For Flavour use for food and feed only

1.3. Details of the supplier of the safety data sheet

Company name: Axxence Aromatic GmbH
Street: Tackenweide 28
Place: D-46446 Emmerich am Rhein
Telephone: + 49 2822 68561 0
E-mail: info@axxence.com
Contact person: Safety Team
E-mail: safety-documentation@axxence.com
Internet: www.axxence.de
Responsible Department: Safety Management

Telefax: + 49 2822 68561 39

Telephone: + 49 2822 68561 0

1.4. Emergency telephone number:

+49 2822 68561 99

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NATURAL ISOBUTYL ACETATE

Revision date: 26.03.2025

Product code: 217500

Page 2 of 12

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P370+P378	In case of fire: Use alcohol resistant foam/Carbon dioxide (CO ₂) to extinguish.
P233	Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to organic waste.

Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

This substance is not listed as Substance of Very High Concern (SVHC) in the Candidate List according to REACH, Article 59.

This substance is not identified as SVHC (substance of very high concern) and is not subject to authorisation according to Annex XIV of REACH.

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula:	C ₆ H ₁₂ O ₂
Molecular weight:	116,16 g/mol

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
110-19-0	NATURAL ISOBUTYL ACETATE			100 %
	203-745-1	607-026-00-7		
	Flam. Liq. 2, STOT SE 3; H225 H336 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
110-19-0	203-745-1	NATURAL ISOBUTYL ACETATE	100 %
	inhalation: LC ₅₀ = 30 mg/l (vapours); dermal: LD ₅₀ = >17400 mg/kg; oral: LD ₅₀ = 13413 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NATURAL ISOBUTYL ACETATE

Revision date: 26.03.2025

Product code: 217500

Page 3 of 12

ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NATURAL ISOBUTYL ACETATE

Revision date: 26.03.2025

Product code: 217500

Page 4 of 12

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Manufacturing of: - Air care products - Perfumes, fragrances - Pharmaceuticals - Cosmetics, personal care products - Flavouring Substances - Other

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
110-19-0	Isobutyl acetate	50	241		TWA (8 h)	
		150	723		STEL (15 min)	

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
110-19-0	NATURAL ISOBUTYL ACETATE			
Worker DNEL, long-term	inhalation	systemic	300 mg/m ³	
Worker DNEL, acute	inhalation	systemic	600 mg/m ³	
Worker DNEL, long-term	inhalation	local	300 mg/m ³	
Worker DNEL, acute	inhalation	local	600 mg/m ³	
Consumer DNEL, long-term	inhalation	systemic	35,7 mg/m ³	
Consumer DNEL, acute	inhalation	systemic	300 mg/m ³	
Consumer DNEL, long-term	inhalation	local	35,7 mg/m ³	
Consumer DNEL, acute	inhalation	local	300 mg/m ³	
Worker DNEL, long-term	dermal	systemic	10 mg/kg bw/day	
Worker DNEL, acute	dermal	local	10 mg/person/day	
Consumer DNEL, long-term	dermal	systemic	5 mg/kg bw/day	
Consumer DNEL, acute	dermal	systemic	5 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	5 mg/kg bw/day	
Consumer DNEL, acute	oral	systemic	5 mg/kg bw/day	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NATURAL ISOBUTYL ACETATE

Revision date: 26.03.2025

Product code: 217500

Page 5 of 12

PNEC values

CAS No	Name of agent	
Environmental compartment		Value
110-19-0	NATURAL ISOBUTYL ACETATE	
Freshwater		0,17 mg/l
Freshwater (intermittent releases)		0,34 mg/l
Marine water		0,017 mg/l
Freshwater sediment		0,877 mg/kg
Marine sediment		0,0877 mg/kg
Micro-organisms in sewage treatment plants (STP)		200 mg/l
Soil		0,075 mg/kg

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable gloves type Butyl caoutchouc (butyl rubber) (0,7mm)

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing .

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless
Odour:	fruity
Melting point/freezing point:	-99 °C
Boiling point or initial boiling point and boiling range:	117 °C
Flammability:	not applicable not applicable
Lower explosion limits:	1,25 vol. %
Upper explosion limits:	10,5 vol. %
Flash point:	22 °C

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NATURAL ISOBUTYL ACETATE

Revision date: 26.03.2025

Product code: 217500

Page 6 of 12

Auto-ignition temperature:	430 °C
Decomposition temperature:	not determined
pH-Value (at 20 °C):	6,7
Viscosity / kinematic: (at 20 °C)	0,8 mm²/s
Water solubility: (at 20 °C)	5,6 g/l
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	2,3
Vapour pressure: (at 20 °C)	19,9 hPa
Vapour pressure: (at 50 °C)	87,7 hPa
Density (at 20 °C):	0,87 g/cm³
Relative vapour density: (at 20 °C)	4,01

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive. not explosive according to EU A.14

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:

not determined

Solvent content:

0%

Solid content:

0%

Viscosity / dynamic:

0,7 mPa·s

(at 20 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NATURAL ISOBUTYL ACETATE

Revision date: 26.03.2025

Product code: 217500

Page 7 of 12

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
110-19-0	NATURAL ISOBUTYL ACETATE				
	oral	LD50 mg/kg	13413	Rat	REACH registration OECD 401
	dermal	LD50 mg/kg	>17400	Rabbit	REACH registration OECD 402
	inhalation (4 h) vapour	LC50	30 mg/l	Rat	REACH registration OECD 403

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (NATURAL ISOBUTYL ACETATE)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification according to Regulation (EC) No 1272/2008 [CLP]: Health hazard properties

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NATURAL ISOBUTYL ACETATE

Revision date: 26.03.2025

Product code: 217500

Page 8 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
110-19-0	NATURAL ISOBUTYL ACETATE					
	Acute fish toxicity	LC50 mg/l	16,6	96 h	Oryzias latipes (Ricefish)	REACH registration
	Acute algae toxicity	ErC50	397 mg/l	72 h	Pseudokirchneriella subcapitata	REACH registration
	Acute crustacea toxicity	EC50 mg/l	24,6	48 h	Daphnia magna (Big water flea)	REACH registration
	Algae toxicity	NOEC	95 mg/l	3 d	Pseudokirchneriella subcapitata	
	Crustacea toxicity	NOEC mg/l	23,2	21 d	Daphnia magna (Big water flea)	REACH registration
	Acute bacteria toxicity	EC50 mg/l ()	1886	0 h	Pseudomonas putida	REACH registration

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
110-19-0	NATURAL ISOBUTYL ACETATE			
	OECD 301D	60%	5	REACH registration
	Readily biodegradable (according to OECD criteria).			
	OECD 301D	74%	10	REACH registration
	Readily biodegradable (according to OECD criteria).			
	OECD 301D	81%	20	REACH registration
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
110-19-0	NATURAL ISOBUTYL ACETATE	2,3

BCF

CAS No	Chemical name	BCF	Species	Source
110-19-0	NATURAL ISOBUTYL ACETATE	15,3		REACH registration

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

The product has not been tested.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NATURAL ISOBUTYL ACETATE

Revision date: 26.03.2025

Product code: 217500

Page 9 of 12

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - used product

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1213
14.2. UN proper shipping name: ISOBUTYL ACETATE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Other applicable information (land transport)
E2

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1213
14.2. UN proper shipping name: ISOBUTYL ACETATE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 1 L
Excepted quantity: E2

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NATURAL ISOBUTYL ACETATE

Revision date: 26.03.2025

Product code: 217500

Page 10 of 12

Other applicable information (inland waterways transport)

E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1213
14.2. UN proper shipping name: ISOBUTYL ACETATE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: -
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1213
14.2. UN proper shipping name: ISOBUTYL ACETATE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Directive 2010/75/EU on industrial emissions: 100 % (870 g/l)

Directive 2004/42/EC on VOC in paints and varnishes: 100 % (870 g/l)

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NATURAL ISOBUTYL ACETATE

Revision date: 26.03.2025

Product code: 217500

Page 11 of 12

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,15,16.

Abbreviations and acronyms

Flam. Liq: Flammable liquid
STOT SE: Specific target organ toxicity - single exposure
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

NATURAL ISOBUTYL ACETATE

Revision date: 26.03.2025

Product code: 217500

Page 12 of 12

H336

May cause drowsiness or dizziness.

EUH066

Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	For Flavour use for food and feed only	-	-	-	-	-	-	-	Flavour

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions